

DECLARATION OF PERFORMANCE

According to Regulation (EU) No. 305/2011

DoP No.: GT-DOP-201

1. Unique identification code of the product-type:

PRIMED PLYWOOD

Thicknesses: 18MM Widths: <=1250MM Lengths: <=2500MM

2. Type, batch or serial number:

See parcel number

3. Intended use:

Use of Non-Structural/Structural Components indoor in dry environments

4. Manufacturer:

Group Thys NV, Kapelsestraat 127, 2950 Kapellen, Belgium, info@grouphys.com

5. Authorised representative:

Not applicable.

6. System of assessment and verification of constancy of performance:

System 2+ 0407-CPR-2008

ISTITUTO GIORDANO S.P.A

7. Harmonised standard / Notified body:

TZU, Notified Body 1021 Performed Initial Type Testing under System 3 issued Performance Assessment Protocol 1021-CPR-23/1230

8. Declared performance

Essential characteristics	Performance	Harmonised standard
Density	640+/-10KG/M3	
Reaction to Fire	Thickness >= 9 mm d-s2,d0	EN 13986
Bending Strength classes 0°/90°	F20/F25	
Bending modulus classes 0°/90°	E25/E35	
Punch Shear Shear (for floors and roofs)	Not applicable	EN 12871
Bracing Strength (for walls)	Not applicable	EN 1995-1-1
Impact Resistance (for floors, roofs and walls)	Not applicable	EN 12871
Water Vapor Permeability	NPD	EN 13986 +A1 : 2015
Formaldehyde release	E05	EN 717-1
Pentachlorophenol content	<=5ppm	EN 13986 +A1 : 2015
Airborne Noise Insulation	NPD	EN 13986 +A1 : 2015

DECLARATION OF PERFORMANCE

According to Regulation (EU) No. 305/2011

DoP No.: GT-DOP-201

Essential characteristics	Performance	Harmonised standard
Sound absorption coefficient	NPD	EN 13986 +A1 : 2015
Thermal Conductivity	NPD	EN 13986 +A1 : 2015
Air permeability	NPD	EN 12114
Bonding Strength	EN 314-2 class 1	EN 314-2
Internal cohesion	NPD	EN 319
Swelling in thickness	NPD	EN 317
Moisture Resistance	See bonding strenght	EN 314-2
Mechanical Durability	NPD	EN 1156
Biological Sustainability	DC3	EN 350

9. Declaration

The performance of the product identified above is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Tiffany Thys, CEO

